


BL Series Lokmalı Hidrolik Tork Anahtarları Square Drive Hydraulic Torque Wrench

- Çalışma basıncı 800 bar maksimum
- Sürekli tekralanabilen torklama hassasiyeti $\pm 2,5$
- 60 Nm den 27.000 Nm ye kadar 9 farklı model
- 360° çok pozisyonlu dönebilir yağ giriş bağlantısı
- Her iki yöne vidalanabilen ergonomik tutma kolu
- Kilit mekanizmalı iki farklı, 360° dönebilir destek ayağı
- Çelik gövdesiyle ağır şartlarda sıkma ve sökmeye uygun tasarımı
- 5.000 Nm ye kadar tek veya çift hortumlu model seçenekleri
- Tek düğme ile değiştirilebilir kare-alyan sürücü adaptörleri
- Türkiye'de servis - kalibrasyon ve yedek parça desteği
- Working pressure 800 bar maximum
- Designed to tighten and loosen nuts requiring high torque
- 9 different model from 60 Nm up to 27.000 Nm torque power
- Constantly repeated accuracy $\pm 2,5\%$ across the full stroke
- 360° multi-positional swivel quick release couplings
- Easy replaceable square and hexagon drive adapters
- Suitable for continuous operation at maximum pressure
- Up to 5000 Nm single and twin hydraulic hose system available
- 360° Adjustable reaction arm with safety lock feature



Tip Type	Tork Gücü Torque (Nm)		Kare Sürücü Square Drive	Ağırlık Weight (kg)	Hortum (Tek-Çift) Connection System	Ölçüler / Sizes (mm)									
	Max	Min				A	B	C	D	E	F	G	I	R	
BL-11	1.000	60	¾"	1,8	O	120	74	51	80	52	37	69	31	22	
BL-31	3.000	220	1"	4	O	140	99	41	100	64	55	99	36	25	
BL-32	3.000	220	1"	4,4	OO	140	99	42	100	64	55	99	36	25	
BL-51	4.900	320	1" - 1½"	5	O	156	114	42	120	81	65	119	40	29	
BL-52	4.900	320	1½"	5,4	OO	167	116	58	120	81	65	119	40	30	
BL-82	8.000	350	1½"	7,8	OO	189	131	59	132	94	70	126	48	41	
BL-102	10.000	440	1½"	7,8	OO	189	131	59	132	94	70	126	48	41	
BL-152	15.200	950	1½" - 2½"	12	OO	224	156	57	152	90	78	135	55	46	
BL-272	27.000	1.500	1½" - 2½"	21	OO	260	193	57	198	118	115	184	70	58	

