

TEWS Series | Açılı Tip Elektrikli Hidrolik Tork Anahtarları

Angle Electrical Torque Wrench

- Sürekli tekrarlanabilen torklama hassasiyeti $\pm 3,5$
- 12.000 Nm'ye kadar sıkma ve sökme kapasitesi
- 200 farklı tork seçeneğine sahip 8 farklı model
- Ayarlanan tork değerinde ulaştığında durma özelliği
- İki vites seçeneği ile hızlı ve yavaş torklama imkanı
- 220 veya 110 Volt 50/60 Hz elektrik motoru seçeneği
- Yoğun ve ağır torklama işlemlerine uygun teknoloji
- Her cihaza özgü seri numarası ve kalibrasyon belgesi
- Türkiye'de servis desteği ve kalibrasyon hizmeti

- *Constantly repeated accuracy $\pm 3,5\%$ with cut off system*
- *Tightening and loosening capacity up to 12.000 Nm*
- *200 different adjustable torque value available*
- *Maschine stops when selected torque value achieved*
- *2 speed gear mechanism for slow and fast operations*
- *Suitable design for heavy duty bolt tightening operations*
- *Both 220 and 110 volt operation power available*
- *Serial number and calibration certificate for each tool*



Sevkiyat İçeriği; Tork anahtarı, kalibrasyon sertifikası, standart destek ayağı, tork seçim tablosu, civata torklama tablosu, kullanım klavuzu, metal taşıma çantası.
Delivery Content; Torque wrench, standart reaction arm, certificate of calibration, torque table, bolt quality torque table, manual instruction, metal carrying case.



Model (Standart Seri / Standart Series)		TEWS-84	TEWS-104	TEWS-244	TEWS-354	TEWS-504	TEWS-604	TEWS-904
Tork Gücü / Torque power (Max)	Nm	850	1.200	2.500	3.500	5.000	6.000	10.000
Tork Gücü / Torque power (Min.)	Nm	150	280	360	360	700	800	1.024
Kare sürücü / Square drive	A inç	3/4"- 1"	1"	1"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
Şanzıman çapı / Out. Diam.	D mm	88	88	88	88	88	130	130
Cihaz boyu / Height	H mm	275	275	305	315	365	350	390
Cihaz genişlik / Width	B mm	395	395	395	395	395	395	395
Net ağırlık / Weight	kg	9,5	9,9	11,5	12,3	14,4	18	20,8
Destek ayağı / Reaction arm	kg	1,6	1,6	1,6	3,5	3,5	5,7	5,7
Boşta dönüş hızı / Idle speed	d/d	16	14	10	9	3	6,5	2,5

Model (Ağır İş Serisi / Heavy Duty Series)		TEWS-85	TEWS-105	TEWS-245	TEWS-355	TEWS-505	TEWS-605	TEWS-905	TEWS-1205
Tork Gücü / Torque power (Max)	Nm	850	1.200	2.500	3.500	5.000	6.000	10.000	12.000
Tork Gücü / Torque power (Min.)	Nm	150	280	360	360	700	800	1.024	1.400
Kare sürücü / Square drive	A inç	3/4"- 1"	1"	1"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"
Şanzıman çapı / Out. Diam.	D mm	99	99	99	99	99	135	135	172
Cihaz boyu / Height	H mm	275	275	305	315	365	350	390	400
Cihaz genişlik / Width	B mm	395	395	395	395	395	395	395	395
Net ağırlık / Weight	kg	9,9	10,1	12,5	13,3	15,5	18,8	22,4	31
Destek ayağı / Reaction arm	kg	1,6	1,6	1,6	3,5	3,5	5,7	5,7	5,7
Boşta dönüş hızı / Idle speed	d/d	16	14	10	9	3	6,5	2,5	2

