

S Series

Lokmalı Hidrolik Tork Anahtarları Square Drive Hydraulic Torque Wrench

- 700 bar maksimum çalışma basıncı
 - Sürekli tekrarlanabilen torklama hassasiyeti $\pm 3\%$
 - 170 Nm den 37.000 Nm ye kadar 5 farklı model
 - İnce diş çark sayesinde boşlama mandalına gerek kalmaz
 - $360^\circ \times 180^\circ$ çok pozisyonlu dönebilir yağ giriş bağlantısı
 - Tek düğme ile değiştirilebilir kare-alyan sürücü adaptörleri
 - Güvenlik kilitli 360° dönebilir alüminyum destek ayağı
 - Gövdeye lazerle işlenmiş (bar / psi) basınç-tork tablosu
 - Alüminyum-titanyum alaşımlı tek parça hafif gövde
 - Türkiye'de servis - kalibrasyon ve yedek parça desteği
- Working pressure 700 bar maximum
 - Designed to tighten and loosen nuts requiring high torque
 - 5 different model from 170 Nm up to 37.000 Nm torque power
 - Constantly repeated accuracy $\pm 3\%$ across the full stroke
 - $360^\circ \times 180^\circ$ multi-positional swivel quick release couplings
 - Easy replaceable square and hexagon drive adapters
 - Body shroud engraved with torque pressure chart
 - Suitable for continuous operation at maximum pressure
 - High resistance & long life with aluminum-titanium light body
 - 360° Adjustable reaction arm with safety lock feature



Tip Type	Tork Gücü / Torque (Nm)		Kare Sürücü Square Drive	Ağırlık Weight (kg)	Ölçüler / Sizes (mm)							
	Max	Min			L1	L2	H1	H2	H3	H4	R	
S 17	1.700	170	3/4"	1,9	129	167	51	73	90	131	25	
S 45	4.500	450	1"	4,8	167	218	68	98	121	170	34	
S 100	10.000	1.000	1 1/2"	9	223	293	92	135	163	211	46	
S 150	15.000	1.500	1 1/2"	14,8	246	323	100	141	177	225	50	
S 370	37.000	3.700	2 1/2"	32,5	329	432	137	104	240	288	66	

